NECA High School Competition

Inspection Check Sheet 2024

| School | Name:_ | | | | | | | Race Date:_ | | | _/ |
|------------|---|--|--|---|---|--|----------------------------------|----------------------------------|--------|-----|-------|
| | Stock | Open | | | If Sto | ock, price l | ist recei | ved? Yes | No | | |
| Car Nu | mber: | | | | | | | | | | |
| Drivers | Names | • | | | | | | | | | |
| Inspect | tor #1:_ | | | | | | _ (Drive | r/Car Stru | cture | and | Specs |
| Driver | | | | | | | | | | | |
| 0000 | The dr Racing Signed Shoes Driver | iver has gogg garment (lor liability relea 's License Nur weight with l | mber: pallast (160 lb | mask, fac sleeve sh s. minimu | ce shield, o nirt), upper um): | r safety gla and lower (if av | asses. must o | | | | |
| | • Roll ba | Communica Ballast mus r must be no | not be perfor ation device/d t be removables than 2" a e car unaided. | ata logge le from ca bove heli | ers do not co ar. | | | | | | |
| Vehicle | • | | | | | | | | | | |
| 0000000000 | Axles a Body S No Sha Vehicle Minim Maxim Maxim Vehicle Tires: I Inflation | g circle less thend spindles of hell arp/Exposed be Numbers aroum track wide um vehicle we weighs minimum 30 on pressure n | Edges (doesn'e 15 cm tall (6 th of 90 cm. vidth of 1.5 mength of 4.0 mength of 1.5 men | t say expo 5") on bot 5" without Maximun ecommer | osed, but se th sides of t driver, balla n 70 cm dia | eems como the car. ast, radio, ameter. Mu | mon ser or batte ust be in | nse Rule 2 ries. flatable. | , Sec. | | |
| 0000 | Two w Inspec | heels must book to crucial faste to crucial faste to community to comm | r pins used or e braked. eners/fittings f ctural integrity Fail | or security and stat | ty. | | be tapp | oed. | | | |

NECA High School Competition

Inspection Check Sheet 2024

| School | Name:_ | | Race Date://_ | |
|---------|--|--|--------------------------------|-----|
| Inspect | or #2: | | (Electrical Equipment/Inside C | ar) |
| | Two iso | olation switches or one switch with two actuators, on The switches or actuators (internal and external) mu turn them to the OFF position. | | |
| | Fuse of Wiring Electric Batteri Battery Last yes 5 point Roll Ba Roll ba All gea Driver' | g system well insulated recircuit breaker between battery and motor. It doesn't specify to negative terminal. It doesn't specify mounted, boxes mounted to frame. It was securely mounted, boxes mounted to frame. It was securely mounted, boxes mounted to frame. It was specify to negative terminal. It was specify to negative terminal terminal specify the secure of the secur | ney are not heated. | |
| | Driver | seat attaches to sub-structure connecting to the roll or shelts are guarded. | cage or frame. | |
| Inspect | or Com | ments: | | |
| | | | | |
| | | | | |
| | | | | |